VEVR

Shanghai Gubotong Tire Co., Ltd.

Product Specifications Catalog



Reliable Quality | Excellent Performance | Safer Driving | Greener Future

About the Company

Shanghai Gubotong Tire Co., Ltd. specializes in the R&D and manufacturing of passenger car radial tires. Equipped with internationally leading production and testing facilities, as well as an experienced team for technical R&D and market operation, we focus on high-performance tire products featuring environmental friendliness, riding comfort and safety.

Adhering to the business principle of **"Market-oriented, Customer First"**, the company adopts a differentiated product strategy to deeply explore market demands, precisely engage global customers, and continuously supply high-quality tire products tailored to market requirements.

Contact & Address

info@campintal.com

https://www.campintal.com/

No.17 Yuejiang Road, Hexi District, Tianjin, China (Chentang Sci-Tech Park)



C16 Series

All-Season | Safety | Performance

Economy all-season tire for city sedans, delivering balanced wet/dry grip with low rolling resistance for everyday commuting.

No.	Brand	Size	Load Index	Speed	Load Range	Max Load (kg)	Pressure (PSI)	Max Speed	Rim
1	VEVR	**165/70R13**	79	T	SL	437	35	190 km/h	5.0J
2	VEVR	**175/70R12**	80	T	SL	450	35	190 km/h	5.0J
3	VEVR	**175/70R13**	82	T	SL	475	35	190 km/h	5.5J
4	VEVR	**185/65R14**	86	H	SL	530	35	210 km/h	5.5J
5	VEVR	**185/70R13**	86	H	SL	530	35	210 km/h	5.5J
6	VEVR	**185/70R14**	88	H	SL	560	35	210 km/h	5.5J
7	VEVR	**195/60R15**	88	H	SL	560	35	210 km/h	6.0J
8	VEVR	**195/65R15**	91	H	SL	615	35	240 km/h	6.0J
9	VEVR	**205/60R16**	92	H	SL	630	35	240 km/h	6.5J
10	VEVR	**205/65R15**	94	H	SL	670	35	240 km/h	6.0J

V19 Series

All-Season | Safety | Performance



High-performance sport tire engineered for drivers who demand precise cornering, responsive steering and high-speed stability.

No.	Brand	Size	Load Index	Speed	Load Range	Max Load (kg)	Pressure (PSI)	Max Speed	Rim
1	VEVR	**165/70R13**	79	T	SL	437	35	190 km/h	5.0J
2	VEVR	**175/70R13**	82	T	SL	475	35	190 km/h	5.0J
3	VEVR	**205/65R15**	94	H	SL	670	35	240 km/h	6.0J
4	VEVR	**205/60R16**	92	H	SL	630	35	240 km/h	6.5J
5	VEVR	**225/60R17**	99	H	SL	775	41	240 km/h	7.0J



V16 Series

All-Season | Safety | Performance

All-terrain tire designed for drivers who demand exceptional off-road grip, confident snow performance, and long-lasting durability.

No.	Brand	Size	Load Index	Speed	Single / Dual Load		Pressure (PSI)	Ply Rating (PR)	Section With(mm)
					KG	LBS			
1	VEVR	LT285/70R17	126/123Q	Q	1700/1550	3748/3417	80	10PR/LOAD RANGE E	292
2	VEVR	LT265/70R17	123/120Q 121/118Q	Q	1550/1400 1450/1320	3417/3086 3197/2910	80	10PR/LOAD RANGE E	272
3	VEVR	LT275/70R18	125/122Q	Q	1650/1500	3638/3307	80	10PR/LOAD RANGE E	279
4	VEVR	LT275/65R18	123/120R	R	1550/1400	3417/3086	80	10PR/LOAD RANGE E	279
5	VEVR	LT265/65R18	122/119R	R	1500/1360	3307/2998	80	10PR/LOAD RANGE E	272
6	VEVR	LT315/70R17	126/123Q	Q	1700/1550	3748/3417	80	10PR/LOAD RANGE E	323
7	VEVR	LT265/75R16	123/120R	R	1550/1400	3417/3086	80	10PR/LOAD RANGE E	267
8	VEVR	LT275/55R20	120/117Q	Q	1400/1285	3086/2833	80	10PR/LOAD RANGE E	284
9	VEVR	LT265/55R19	118/115S	S	1320/1215	2910/2679	80	10PR/LOAD RANGE E	277
10	VEVR	LT265/60R18	119/116R	R	1360/1250	2998/2756	80	10PR/LOAD RANGE E	272
11	VEVR	35x12.5R20LT	121Q	Q	1450	3197	65	10PR/LOAD RANGE E	318

AT255 Series

An interlocking block-pattern design, combined with wide grooves, creates a robust tread structure that balances superior grip with the ability to navigate complex road conditions—unlocking greater potential for light-truck transport.

All-Season | Safety | Performance

No.	Brand	Size	Load Index	Speed	RIM	Max.load kg(lbs)	Section width	Max pressure kpa(psi)
1	VEVR	**245/70R16**	107	S	7J	975(2149)	248	300(44)
2	VEVR	**265/70R16**	112	T	8J	1120(2469)	272	300(44)
3	VEVR	**275/70R16**	114	T	8J	1180(2601)	279	300(44)
4	VEVR	**245/65R17**	107	T	7J	975(2149)	248	300(44)
5	VEVR	**255/65R17**	110	T	7½J	106(2337)	260	300(44)
6	VEVR	**265/65R17**	112	T	8J	1120(2469)	272	300(44)
7	VEVR	**265/70R17**	115	S	8J	1215(2679)	272	300(44)
8	VEVR	**275/65R17**	115	T	8J	1215(2679)	279	300(44)
9	VEVR	**285/65R17**	116	T	8½J	1250(2756)	292	300(44)
10	VEVR	**235/60R18**	103	T	7J	875(1929)	240	300(44)
11	VEVR	**255/60R18**	108	T	7½J	1000(2205)	260	300(44)
12	VEVR	**265/60R18**	110	T	8J	1060(2337)	272	300(44)
13	VEVR	**265/65R18**	114	T	8J	1180(2601)	272	300(44)
14	VEVR	**285/60R18**	116	T	8½J	1250(2756)	292	300(44)
15	VEVR	**225/70R17**	108	T	6½J	1000(2205)	228	340(50)
16	VEVR	**225/70R17C**	112/110	S	6½J	120(2470)/1060(2335)	228	375(55)





AT200 Series

All-Season | Safety | Performance

Rugged tread blocks combined with deep, longitudinal grooves create a distinct, multi-layered tread structure that balances road-gripping traction with durability.

No.	Brand	Size	Load Index	Speed	Ply Rating	RIM	Max.load kg(lbs)	Section width	Max pressure kpa(psi)
1	VEVR	**31x10.5R15LT**	109	Q	6	8½J	975(2149)	268	350(51)
2	VEVR	**LT215/75R15**	100/97	S	6	6J	1120(2469)	216	350(50)
3	VEVR	**LT235/75R15**	104/101 116/113	S S	6 10	6½J	1180(2601)	235 235	350(50) 550(80)
4	VEVR	**LT225/75R16**	115/112	S	10	6J	975(2149)	223	550(80)
5	VEVR	**LT235/85R16**	120/116	S	10	6½J	106(2337)	235	550(80)

AT300 Series

All-Season | Safety | Performance



Combining a rugged appearance with the ability to adapt to diverse terrain, the AT300 is the ideal choice for drivers who seek both confidence behind the wheel and the joy of exploration.

No.	Brand	Size	Load Index	Speed	Ply rating	RIM	Max.load kg(lbs)	Section width	Max pressure kpa(psi)
1	VEVR	**235/60R16**	100	T		7J	800(1764)	240	300(44)
2	VEVR	**245/70R16**	107	T		7J	975(2150)	245	300(44)
3	VEVR	**265/70R16**	112	T		8J	1120(2469)	272	300(44)
4	VEVR	**245/65R17**	107	T		7J	975(2150)	248	300(44)
5	VEVR	**265/65R17**	112	T		8J	1120(2469)	272	300(44)
6	VEVR	**265/70R17**	115	S		8J	1215(2679)	272	300(44)
7	VEVR	**265/60R18**	110	T		8J	1060(2337)	272	300(44)
8	VEVR	**LT215/75R14**	98/95	S	8	6J	900(1984)/825(1819)	216	450(65)
9	VEVR	**27*8.5R14LT**	95	Q	6	7J	690 (1521)	210	350(50)
10	VEVR	**LT245/70R16**	113/110	Q	10	7J	1150(2535)/1060(2337)	248	450(65)

No.	Brand	Size	Load Index	Speed	Ply rating	RIM	Max.load kg(lbs)	Section width	Max pressure kpa(psi)
11	VEVR	**LT245/75R16**	120/116	R	10	7J	1380/1260/(3042/2778)	248	550(80)
12	VEVR	**LT265/70R16**	117/114	Q	10	8J	1285(2835)/1180(2000)	272	450(65)
13	VEVR	**LT265/75R16**	123/120	R	10	7.5J	1550/1400(3417/3086)	267	550(80)
14	VEVR	**LT245/65R17**	111/108	Q	8	7J	1090(2405)1000(2205)	248	450(65)
15	VEVR	**LT265/65R17**	120/117	S	10	8J	1400(3085)/1285(2835)	272	550(80)
16	VEVR	**LT265/70R17**	118/115	S	8	8J	1320(2910)/1215(2680)	272	450(65)
17	VEVR	**LT285/65R17**	121/118	S	10	8½J	1450(3195)/1320(2910)	292	550(80)
18	VEVR	**LT285/70R17**	122/119	S	8	8½J	1500(3305)/1360(3000)	292	450(65)
			121/118		10		1450(3195)/1320(2910)		550(80)
19	VEVR	**LT315/70R17**	121/118	S	8	9½J	1450(3195)/1320(2910)	323	350(50)
20	VEVR	**LT265/60R18**	119/116	S	10	8J	1360(3000)/1250(2755)	272	550(80)



ZT801 Series

All-Season | Safety | Performance

Wavy longitudinal grooves combined with fine transverse patterns create a unique tread layout, balancing ride smoothness with road surface adaptability.

No.	Brand	Size	Load Index	Speed	Ply rating	Section width	Pressure (PSI)	Max.load kg(lbs)	Rim
1	VEVR	**5.00R12LT**	88/86	P	10	143	550(80)	560(1235)/530(1170)	3.50B
2	VEVR	**5.50R12LT**	92/90	P	10	160	550(73)	630(1389)/600(1323)	3.50B
3	VEVR	**5.50R13LT**	94/92	P	12	160	550(80)	670(1480)/640(1410)	4.00B

ZT802 Series

All-Season | Safety | Performance



The combination of irregular block patterns and multi-directional grooves lends the tread a distinct sense of power, with a robust design that meets the diverse transport requirements of light trucks.

No.	Brand	Size	Load Index	Speed	Ply rating	Section width	Pressure (PSI)	Max.load kg(lbs)	Rim
1	VEVR	**5.00R12LT**	88/86	P	10	143	550(80)	560(1235)/530(1170)	3.50B
2	VEVR	**5.50R12LT**	92/90	P	10	160	550(73)	630(1389)/600(1323)	3.50B
3	VEVR	**5.50R13LT**	94/92	P	12	160	550(80)	670(1480)/640(1410)	4.00B



LIGHT TRUCK TIRE
ZT901 Series

All-Season | Safety | Performance

Dynamic curves and intersecting grooves complement one another, creating a multi-layered tread pattern that balances road adaptability with driving stability.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**155R12C**	88/86	Q	8	560(1235)/530(1168)	450(65)	4.50B
2	VEVR	**155R13C**	90/88	Q	8	600(1323)/560(1235)	450(65)	4.50B
3	VEVR	**165R13C(ZT101)**	94/93	N	8	670(1477)/650(1433)	450(65)	4.50B
4	VEVR	**175R13C**	97/95	Q	8	730(1609)/690(1521)	450(65)	5.00B

ZT501 Series

All-Season | Safety | Performance



The clever combination of diamond-shaped tread blocks and longitudinal grooves creates a multi-layered tread structure, ensuring both road grip and driving stability.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**185R14C**	102/100	S	8	850(1875)/800(1764)	450(65)	5½J
2	VEVR	**185R15C**	103/102	S	8	875(1929/850(1875)	450(65)	5½J
3	VEVR	**195R14C**	106/104	S	8	950(2095)/900(1985)	450(65)	5½J
4	VEVR	**195R15C**	106/104	S	8	950(2095)/900(1985)	450(65)	5½J

ZT 502 Series



Intricate, multidirectional tread patterns are arranged to create a balanced layout, ensuring both strong grip and driving stability.

No.	Brand	Size	Load Index	Speed	Ply rating	Section width	Pressure (PSI)	Max.load kg(lbs)	Rim
1	VEVR	**195R15C**	106/104	S	8	198	550(80)	950(2095)/900(1985)	5½J



ZT505 Series

All-Season | Safety | Performance

Featuring a design with rugged, block-style tread patterns and deep grooves, the tire offers enhanced road grip, while balancing durability with adaptability to diverse road conditions.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	195R14C	106/104	S	8	950(2095)/900(1985)	450(65)	5½J
2	VEVR	195R15C	106/104	S	8	950(2095)/900(1985)	450(65)	5½J



ZT506 Series

All-Season | Safety | Performance

The design, featuring fluid grooves combined with a rhythmic tread pattern, ensures both effective water drainage and driving stability.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	195R14C	106/104	S	8	950(2095)/900(1985)	450(65)	5½J
2	VEVR	195R15C	106/104	S	8	950(2095)/900(1985)	450(65)	5½J

ZT701 Series

All-Season | Safety | Performance



The tire features a robust tread pattern with a three-dimensional interlocking design, balancing road grip and driving performance.

No.	Brand	Size	Load Index	Speed	Ply rating	RIM	Max.load kg(lbs)	Section width	Max pressure kpa(psi)
1	VEVR	**175R14LT**	99/97	Q	8	5J	775(1710)/730(1610)	177	450(65)
2	VEVR	**205R14C**	109/107	Q	8	6J	1030(2271)/975(2150)	208	450(65)
3	VEVR	**215R14C**	112/110	Q	8	6J	1120(2470/1060(2337)	216	450(65)
4	VEVR	**185/65R15LT**	94/91	Q	8	5½J	670(1475)615(1355)	189	450(65)
5	VEVR	**195/70R15C**	104/102	R	8	6J	900(1984)850(1874)	201	450(65)
6	VEVR	**205/70R15C**	106/104	S	8	6J	950(2095)900(1985)	209	450(65)
7	VEVR	**215/65R15C**	104/102	R	8	6½J	900(1985)/850(1875)	221	375(55)
8	VEVR	**215/70R15C**	109/107	R	8	6½J	1030(2271)975(2150)	221	450(65)
9	VEVR	**225/70R15C**	112/110	R	8	6.5J	1120(2469)/1060(2337)	228	450(65)
10	VEVR	**205/65R16C**	107/105	R	8	6J	975(2150)925(2039)	209	450(65)
11	VEVR	**215/65R16C**	109/107	R	8	6½J	1030(2270)975(2150)	221	475(70)
12	VEVR	**215/70R16C**	108/106	N	8	6.5J	1000(2200)950(2090)	221	375(54)
13	VEVR	**215/75R16C**	113/111 116/114	R	8 10	6J	1150(2535)1090(2403) 1250(2756)1180(2601)	216	475(68) 525(76)
14	VEVR	**205R16C**	110/108	Q	8	6J	1215(2678)1150(2535)	208	475(68)
15	VEVR	**235/65R16C**	115/113 121/119	R	8 12	7J	1060(2337)/1000(2205) 1450(3195)/1360(3000)	240	450(65) 575(83)



ZT503 Series

All-Season | Safety | Performance

A tread pattern featuring multiple blocks enhances the contact between the tire and the road surface, ensuring both driving stability and the ability to adapt to complex road conditions.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**255/70R15C**	112/110	S	8	1150(2535)/1060(2335)	450(65)	7.5J
2	VEVR	**205R16C**	110/108	R	8	1060(2337)/1000(2205)	450(65)	6J



ZT206 Series

All-Season | Safety | Performance

The unique block-pattern tread design balances road adaptability with durability, providing a solid foundation for daily light-truck transport and effortlessly meeting diverse operational requirements.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**7.50R16LT**	114/112	R	8	1180(2600) 1120(2470)	475(69)	6.00G

ZT201 Series

All-Season | Safety | Performance



Specifically engineered for light-truck transport, it features a practical tread pattern design that balances driving stability with wear resistance and utility.

No.	Brand	Size	Load Index	Speed	Ply rating	Section width	Pressure (PSI)	Max.load kg(lbs)	Rim
1	VEVR	**6.50R16LT**	107/103	N	10	185	550(80)	975(2150)/875(1930)	5.50F
2	VEVR	**7.00R15LT**	110/105	N	10	200	550(80)	1060(2335)/925(2040)	5.50F
3	VEVR	**7.00R16LT**	115/111	N	12	200	650(95)	1215(2680)/1090(2405)	5.50F
4	VEVR	**7.50R16LT**	123/119	L	14	215	760(110)	1550(3415/1360(3000)	6.00G



ZT207 Series

All-Season | Strong Traction | Performance

Featuring a rugged block-pattern tread for reliable grip and enhanced stability, designed to deliver dependable performance for light trucks in demanding road conditions.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**225/95R16C**	118/116	S	10	1320(2910)1250(2755)	475(69)	6.00G
2	VEVR	**7.50R16LT**	114/112	R	8	1180(2600)1120(2470)	475(69)	6.00G

SAND GRIP TIRE
ZT208 Series

Stable Handling **Excellent Durability** **Reliable Performance**



Featuring a robust block-pattern tread for dependable grip and enhanced stability, designed to tackle demanding desert terrain with confidence.

No.	Brand	Size	Load Index	Speed	Ply rating	Section width	Pressure (PSI)	Max.load kg(lbs)	Rim
1	VEVR	**7.50R16LT**	112/107 120/116	R N	8 12	215	460(65) 650(95)	1120(2470)/975(2150) 1400(3085)/1250(2755)	6.00G

ZT702 Series

Stable Handling **Strong Durability** **Reliable Performance**



Featuring a ribbed tread design for stable directional control and dependable road contact, engineered for reliable performance in demanding desert conditions.

No.	Brand	Size	Load Index	Speed	Ply rating	Section width	Pressure (PSI)	Max.load kg(lbs)	Rim
1	VEVR	**225/95R16C**	118/116	S	10	223	475(69)	1320(2910)1250(2755)	6.00G



ZT703 Series

Stable Traction | **Durable Structure** | **Reliable Performance**

Featuring a dense block-pattern tread for stable road contact and dependable grip, designed to deliver reliable performance in demanding desert conditions.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**185/75R16C**	104/102	R	8	900(1985)/850(1875)	475(69)	5.00J
2	VEVR	**195/75R16C**	107/105	R	8	975(2150)/925(2040)	475(69)	5½J

ZT601 Series

Excellent Traction | **Robust Durability** | **Reliable Performance**



Designed for challenging desert terrain, featuring a durable tread design for dependable grip and stable performance across demanding road conditions.

No.	Brand	Size	Load Index	Speed	Ply rating	Section width	Pressure (PSI)	Max.load kg(lbs)	Rim
1	VEVR	**6.00R13LT**	93/89 98/94	P P	8 10	170	420(61) 530(77)	650(1433)/580(1279) 750(1654)/670(1477)	4.50B
2	VEVR	**6.00R14LT**	95/90 100/96	P P	8 10	170	420(61) 530(77)	690(1521)/600(1323) 800(1764)/710(1566)	4½J
3	VEVR	**6.00R15LT**	97/92 101/97	P P	8 10	170	420(61) 530(77)	730(1609)/630(1389) 825(1819)/730(1610)	4.50E



WINTER LIGHT TRUCK TIRE
ZT205 Series

Enhanced Traction | **Reliable Grip** | **Winter Performance**

Featuring a multi-sipe tread design for improved grip and stable handling in cold-weather conditions, delivering dependable performance for winter transportation.

No.	Brand	Size	Load Index	Speed	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**6.50R16LT**	107/102	L/N	10	975(2150)/850(1875)	560(81)	5.50F
2	VEVR	**7.00R16LT**	117/107	L/N	10	1090(2403)/975(2150)	560(81)	5.50F
			115/110		12	1215(2679)/1060(2337)	670(97)	
3	VEVR	**6.00R13LT**	93/98	P	8	650(1433)/580(1279)	420(61)	4.50B
			98/94	P	10	750(1654)/670(1477)	530(77)	
4	VEVR	**6.00R14LT**	98/90	P	8	690(1521)/600(1323)	420(61)	4½J
			100/96	P	10	800(1764)/710(1566)	530(77)	
5	VEVR	**6.00R15LT**	97/92	P	8	730(1609)/630(1389)	460(67)	4.50E
			101/97	P	10	825(1819)/730(1610)	530(77)	

SPECIAL TRAILER RADIAL TIRE(SRT) ZT301 Series

Excellent Grip | **Stable Handling** | **Durable Performance**

Featuring an optimized tread pattern for reliable traction, enhanced driving stability, and dependable performance across diverse road conditions..

No.	Brand	Size	Rim	Speed	Section width	Overall diameter
1	VEVR	**ST145R12 8PR**	4.00B	88/83L	145	527
2	VEVR	**ST175/80R13 6PR**	5.00B	91/87L	177	610
3	VEVR	**ST185/80R13 8PR**	5J	99/95L	184	626
4	VEVR	**ST205/75R14 6PR**	5½J	100/96L	203	664
5	VEVR	**ST205/75R14 8PR**	5½J	105/101L	203	664
6	VEVR	**ST215/75R14 6PR**	6J	102/98L	216	678
7	VEVR	**ST205/75R15 6PR**	5½J	101/97L	203	689
8	VEVR	**ST205/75R15 8PR**	5½J	107/102L	203	689
9	VEVR	**ST225/75R15 8PR**	6J	113/108L	223	719
10	VEVR	**ST225/75R15 10PR**	6J	117/112L	223	719
11	VEVR	**ST205/90R15 12PR**	5.50F	109/105L	200	750
12	VEVR	**ST225/90R16 8PR**	6J	121/117Q	220	808
13	VEVR	**ST225/90R16 10PR**	6J	124/120L	220	808
14	VEVR	**ST235/80R16 10PR**	6½J	124/120L	235	782
15	VEVR	**ST235/85R16 10PR**	6.5	123/121L	235	806
16	VEVR	**ST235/85R16 12PR**	6.5	128/124L	235	806





ELECTRO—TRICYCLE TIRE

Stable Grip | **Durable Performance** | **Smooth Riding**

Designed for reliable traction and stable handling, delivering dependable performance for everyday transportation and cargo needs.

No.	Brand	Size	Section width	Ply rating	Max.load kg(lbs)	Pressure (PSI)	Rim
1	VEVR	**4.00-10**	105	4	250kg	250	60J
				6	272kg	280	63J
2	VEVR	**5.00-10**	135	6	412kg	280	77J